

RX489

- 4WD TRANSVERSE GEARBOX
- SEQUENTIAL 5 (or 6) SPEED
- TFJ DIFFERENTIAL
- 57 KG



APPLICATION

Rallycross
Rally

TECHNICAL SPECIFICATIONS

5 (or 6) speed dog ring gearbox, with sequential gearing

Maxi engine torque : 800 N.m (590 lbs/ft)

20mm teeth width (1st to 3rd) & 17mm (4th to 6th) - 89 mm on center

Final drive

Gear ratios, wide range

Oil pump & internal lubrication system + steel filter

TFJ self-locking differential : 3 + 3 discs, several ramp angles

Cluster removable

Preload adjustment without disassembly

Specific clutch shaft

Hydraulic release clutch + feeder tubes

Barrel position sensor

Cable to ban reverse gear

Weight : 57 Kg

For each order, our sales department will contact you to define technical specifications (ratio charts, bell housing..)

OPTIONS & ACCESSORIES

TFJ self-locking differential with external preload adjustment

Bellhousing

Gear lever kit

Gear display

Reinforced tripod flange 45 splines

Female flange for lobro propshaft

Cut-off sensor kit on command

FOLLOW US ON WWW.3MO.COM

3MO Performance
36, rue de Bruxelles
ZA Les Bozées
53000 LAVAL
FRANCE

 +33 (0)2.43.53.29.39

 contact@3mo.com